



Comfort sleep



Pressing as button to start the OFF timer operation that automatically adjusts the room temperature and the fan speed.

With its attractive and slim-line design, this high-wall is suitable for offices, restaurants and other applications where elegance is required.

Drain hose can be connected to both side of the unit, increasing the installation flexibility and drain pipe length.

Wireless remote control with pre-set functions accessible with dedicated buttons: hi-power mode, quiet mode, comfort sleep, eco-mode.

Self cleaning feature to prevent mould formation on the heat exchanger coils.

Auto louvre mode allows optimum and uniform air distribution.

HIGH-WALL

DI AND SDI INVERTER

SM_KRT



INDOOR UNITS

RAV-SM564KRT-E
RAV-SM804KRT-E

OUTDOOR UNITS

RAV-SP564AT-E
RAV-SP804AT-E

RAV-SM563AT-E
RAV-SM803AT-E

With branching kits
RAV-SM2244AT8-E
RAV-SM2804AT8-E

REMOTE CONTROLS

Wireless included
Wired
RBC-AM51E-EN(ES)
RBC-AMS41E
RBC-AMT32E
RBC-AS21E2

SM_6KRT + SP_AT

Performance data with Super Digital Inverter

		RAV-SP564AT-E	RAV-SP804AT-E
Outdoor unit		RAV-SM566KRT-E	RAV-SM806KRT-E
Indoor unit (High-wall)		RAV-SM566KRT-E	RAV-SM806KRT-E
Cooling capacity	kW	5,0	7,1
Cooling range (min. - max.)	kW	1,2 - 5,6	1,9 - 8,0
Power input (min. - rated - max.)	kW CO	0,21 - 1,44 - 2,05	0,3 - 2,21 - 2,88
EER		3,47	3,21
Energy efficiency class	CO	A	A
Annual energy consumption	kWh	720	1105
Heating capacity	kW	5,6	8,0
Heating range (min. - max.)	kW	1,5 - 5,6	1,3 - 10,6
Power input (min. - rated - max.)	kW HP	0,17 - 1,50 - 2,57	0,27 - 2,34 - 3,87
CDP		3,73	3,42
Energy efficiency class	HP	A	B

SM_6KRT + SM_AT

Performance data with Digital Inverter

		RAV-SM563AT-E	RAV-SM803AT-E
Outdoor unit		RAV-SM566KRT-E	RAV-SM806KRT-E
Indoor unit (High-wall)		RAV-SM566KRT-E	RAV-SM806KRT-E
Cooling capacity	kW	5,0	6,7
Cooling range (min. - max.)	kW	1,5 - 5,6	1,5 - 8,0
Power input (min. - rated - max.)	kW CO	0,40 - 1,66 - 1,86	0,50 - 2,37 - 2,85
EER		3,01	2,83
Energy efficiency class	CO	B	C
Annual energy consumption	kWh	830	1185
Heating capacity	kW	5,6	8,0
Heating range (min. - max.)	kW	1,5 - 6,3	1,5 - 9,0
Power input (min. - rated - max.)	kW HP	0,40 - 1,64 - 2,40	0,50 - 2,49 - 3,46
CDP		3,41	3,21
Energy efficiency class	HP	B	C

SM_6KRT

Physical data Indoor units

		RAV-SM566KRT-E	RAV-SM806KRT-E
Indoor unit			
Air Flow (h/l)	m ³ /h - l/s	840/660 - 233/183	1020/660 - 283/183
Sound pressure level (H-M-L)	dB(A)	42-39-36	47-41-46
Sound power level (H-M-L)	dB(A)	57-54-51	62-56-51
Dimensions (HxWxD)	mm	320x1050x228	320x1050x228
Weight	kg	12	12

CO = cooling mode
HP = heating mode
H-M-L = High - Medium - Low speed